LED Spot MR16 4W 280lm 6500K 105° GU5.3 G2



PRODUCT INFORMATION

Product code 60318

Product code (long) IE-MR16-4-280-6500K-105-G2

Product description LED Spot MR16 4W 280lm

EAN code 5999097603186

Category Retrofit

PHOTOMETRIC DATA

| Nominal luminous flux | 252 lm |
|---|----------|
| Rated luminous flux | 280 lm |
| Rated useful luminous flux | 70 |
| Nominal beam angle (half-peak value) | 105° |
| Rated beam angle (half-peak value) | 105° |
| Correlated colour temperature | 6500K |
| Colour temperature designation | daylight |
| Colour rendering index (Ra) | 80 Ra |
| Colour consistency | 6 SDCM |
| Warm-up time to reach 60% of full light | 0,5 s |
| Suitable for accent lighting | N |

ELECTRICAL DATA

| Nominal wattage | 4W |
|-------------------------------------|--------|
| Rated wattage | 4W |
| Nominal voltage | 12V |
| Nominal current | 500 mA |
| Power factor | 0.5 |
| Wattage of equivalent filament lamp | 25W |
| | |

Overal diameter 50 mm
Overall height 49 mm
Lamp shape MR16
Weight 0,020 kg

LIFE SPAN

| Nominal life time | 15 000 hrs |
|---|------------|
| Rated life time | 15 000 hrs |
| Number of switching cycles | 12500 |
| Lumen main.fact.at end of nom.life time | 0,7 |
| Warranty | 3 years |

ADDITIONAL TECHNICAL INFORMATION

| Starting time | 0,5 s |
|---------------------------------------|---------------|
| Optimum operating ambient temperature | -10°C - +50°C |
| Lamp cap | GX5.3 |
| Lamp finish | Milky cover |
| Dimming | non-dimmable |
| Energy efficiency class | A+ |
| Energy consumption | 4 kWh/100h |
| IP rating | IP42 |



