DL147 Downlight Square 9W 580lm 3000K 120° G2

PRODUCT INFORMATION

Product code	60346
Product code (long)	IE-DL-DLR150x-9-580-3000K-1
Product description	DL147 Downlight Square 9W
EAN code	5999097603469
Category	Downlight

PHOTOMETRIC DATA

Nominal luminous flux	580 lm
Rated luminous flux	580 lm
Rated useful luminous flux	65
Nominal beam angle (half-peak value)	110°
Rated beam angle (half-peak value)	110°
Correlated colour temperature	3000K
Colour temperature designation	warm white
Colour rendering index (Ra)	80 Ra
Colour consistency	6 SDCM
Warm-up time to reach 60% of full light	2 s
Suitable for accent lighting	N

LIFE SPAN

Nominal life time	30 000 hrs
Rated life time	30 000 hrs
Number of switching cycles	15000
Lumen main.fact.at end of nom.life time	0,7
Warranty	3 years

ELECTRICAL DATA

Nominal wattage	9W
Rated wattage	9W
Nominal voltage	220-240V
Operating frequency	50/60Hz
Nominal current	260 mA
Power factor	0.5

Overal diameter	147 mm
Overall width	21 mm
Lamp shape	Square
Weight	0,280 kg
Mounting	Recessed

ADDITIONAL TECHNICAL INFORMATION

Starting time	3,0 s
Optimum operating ambient temperature	-20°C - +40°C
Lamp finish	Milky cover
Dimming	non-dimmable
Energy efficiency class	A+
Energy consumption	9 kWh/100h
Electrical protection class	Class II
IP rating	IP20



5 999097 603469