60347

INESA

IE-DL-DLR150x-9-580-4000K Ra Product code (long) DL147 Downlight Square 9W N Product description 5999097603476 0 EAN code N Category Downlight Pc 0 PHOTOMETRIC DATA 0 Nominal luminous flux 580 lm La 585 lm Rated luminous flux W Rated useful luminous flux 65 Mounting Nominal beam angle (half-peak value) 110° Rated beam angle (half-peak value) 110° Correlated colour temperature 4000K Colour temperature designation neutral white 80 Ra

6 SDCM

30 000 hrs

30 000 hrs

15000

3 years

0,7

2 s

Ν

PRODUCT INFORMATION

Colour rendering index (Ra)

Suitable for accent lighting

Number of switching cycles

Warm-up time to reach 60% of full light

Lumen main.fact.at end of nom.life time

Colour consistency

Nominal life time

Rated life time

Warranty

LIFE SPAN

Product code

ELECTRICAL DATA

Nominal wattage	9W
Rated wattage	9W
Nominal voltage	220-240V
Operating frequency	50/60Hz
Nominal current	260 mA
Power factor	0.5
Overal diameter	147 mm
Overall width	21 mm
Lamp shape	Square
Weight	0,280 kg
Mounting	Recessed

ADDITIONAL TEC	HNICAL INFORMATION

Starting time	3,0 s
Optimum operating ambient temperature	-20°C - +40°C
Lamp finish	Milky cover
Dimming	non-dimmable
Energy efficiency class	A+
Energy consumption	9 kWh/100h
Electrical protection class	Class II
IP rating	IP20



