DL202 Downlight Square 15W 1000lm 3000K 120° G2

Downlight



PRODUCT INFORMATION

Product code 60349
Product code (long) IE-DL-DLR190x-15-1000-3000K
Product description DL202 Downlight Square 15W
EAN code 5999097603490

PHOTOMETRIC DATA

Category

Nominal luminous flux 1000 lm Rated luminous flux 1000 lm Rated useful luminous flux 67 110° Nominal beam angle (half-peak value) Rated beam angle (half-peak value) 110° Correlated colour temperature 3000K Colour temperature designation warm white 80 Ra Colour rendering index (Ra) 6 SDCM Colour consistency Warm-up time to reach 60% of full light 2 s Suitable for accent lighting

ELECTRICAL DATA

Nominal wattage 15W
Rated wattage 15W
Nominal voltage 220-240V
Operating frequency 50/60Hz
Nominal current 300 mA
Power factor 0.9

Overal diameter 202 mm
Overall width 21 mm
Lamp shape Square
Weight 1,000 kg
Mounting Recessed

LIFE SPAN

Nominal life time 30 000 hrs
Rated life time 30 000 hrs
Number of switching cycles 15000
Lumen main.fact.at end of nom.life time 0,7
Warranty 3 years

ADDITIONAL TECHNICAL INFORMATION

Starting time 3,0 s
Optimum operating ambient temperature -20°C - +40°C
Lamp finish Milky cover
Dimming non-dimmable
Energy efficiency class A+
Energy consumption 15 kWh/100h
Electrical protection class | IP20



