DL301 Downlight Square 36W 2520lm 3000K 120° G2



PRODUCT INFORMATION

Product code 60355 IE-DL-DLR300x-36-2520-3000K Product code (long)

DL301 Downlight Square 36W Product description 5999097603551 EAN code

Category Downlight

ELECTRICAL DATA

Nominal wattage 36 W 36.0 W Rated wattage 220-240V Nominal voltage 50/60Hz Operating frequency 700 mA Nominal current Power factor 0.9

PHOTOMETRIC DATA

Nominal luminous flux 2520 lm 2700 lm Rated luminous flux Rated useful luminous flux 70 Nominal beam angle (half-peak value) 110° Rated beam angle (half-peak value) 110° Correlated colour temperature 3000K Colour temperature designation warm white 80 Ra Colour rendering index (Ra) 6 SDCM Colour consistency Warm-up time to reach 60% of full light 2 s Suitable for accent lighting

MECHANICAL DATA

Overall length 301 mm 301 mm Overall width Overall height 21 mm Lamp shape Sauare Weight 1,600 kg 282 mm x 282 mm cuto Mounting

LIFE SPAN

Nominal life time 30 000 hrs Rated life time 30 000 hrs Number of switching cycles 15000 Lumen main.fact.at end of nom.life time 70% Warranty 3 years

ADDITIONAL TECHNICAL INFORMATION

Starting time 3,0 s -20°C - +40°C Optimum operating ambient temperature Lamp finish Milky cover Dimming non-dimmable Energy efficiency class

36 kWh/100h Energy consumption Class II Electrical protection class IP20 IP rating



