DL301 Downlight Square 36W 2700lm 4000K 120° G2



PRODUCT INFORMATION

Product code 60356
Product code (long) IE-DL-DLR300x-36-2700-4000K
Product description DL301 Downlight Square 36W

EAN code 5999097603568 Category Downlight

ELECTRICAL DATA

Nominal wattage36 WRated wattage36.0 WNominal voltage220-240VOperating frequency50/60HzNominal current700 mAPower factor0.9

PHOTOMETRIC DATA

Nominal luminous flux 2700 lm 2700 lm Rated luminous flux Rated useful luminous flux 75 Nominal beam angle (half-peak value) 110° Rated beam angle (half-peak value) 110° Correlated colour temperature 4000K Colour temperature designation neutral white 80 Ra Colour rendering index (Ra) 6 SDCM Colour consistency Warm-up time to reach 60% of full light 2 s Suitable for accent lighting

MECHANICAL DATA

 Overall length
 301 mm

 Overall width
 301 mm

 Overall height
 21 mm

 Lamp shape
 Square

 Weight
 1,600 kg

 Mounting
 282 mm x 282 mm cuto

LIFE SPAN

Nominal life time30 000 hrsRated life time30 000 hrsNumber of switching cycles15000Lumen main.fact.at end of nom.life time70%Warranty3 years

ADDITIONAL TECHNICAL INFORMATION

Starting time 3,0 s

Optimum operating ambient temperature -20°C - +40°C

Lamp finish Milky cover

Dimming non-dimmable

Energy efficiency class A+

Energy consumption 36 kWh/100h

Electrical protection class Class II

IP rating IP20



