DL301 Downlight Square 36W 2800lm 6000K 120° G2



PRODUCT INFORMATION

Product code 60357

Product code (long) IE-DL-DLR300x-36-2800-6000K

Product description DL301 Downlight Square 36W

EAN code 5999097603575

Category Downlight

PHOTOMETRIC DATA

Nominal luminous flux 2800 lm 2700 lm Rated luminous flux Rated useful luminous flux Nominal beam angle (half-peak value) 110° Rated beam angle (half-peak value) 110° Correlated colour temperature 6000K Colour temperature designation daylight Colour rendering index (Ra) 80 Ra 6 SDCM Colour consistency Warm-up time to reach 60% of full light 2 s Suitable for accent lighting

ELECTRICAL DATA

Nominal wattage36 WRated wattage36.0 WNominal voltage220-240VOperating frequency50/60HzNominal current700 mAPower factor0.9

MECHANICAL DATA

 Overall length
 301 mm

 Overall width
 301 mm

 Overall height
 21 mm

 Lamp shape
 Square

 Weight
 1,600 kg

 Mounting
 282 mm x 282 mm cuto

LIFE SPAN

Nominal life time30 000 hrsRated life time30 000 hrsNumber of switching cycles15000Lumen main.fact.at end of nom.life time70%Warranty3 years

ADDITIONAL TECHNICAL INFORMATION

Starting time 3,0 s
Optimum operating ambient temperature -20°C - +40°C
Lamp finish Milky cover
Dimming non-dimmable
Energy efficiency class A+
Energy consumption 36 kWh/100h
Electrical protection class Class II
IP rating IP20



