INE'S'A

PRODUCT INFORMATION

| Product code |
|---------------------|
| Product code (long) |
| Product description |
| EAN code |
| Category |

PHOTOMETRIC DATA

| Nominal luminous flux |
|-----------------------------------------|
| Rated luminous flux |
| Rated useful luminous flux |
| Nominal beam angle (half-peak value) |
| Rated beam angle (half-peak value) |
| Correlated colour temperature |
| Colour temperature designation |
| Colour rendering index (Ra) |
| Colour consistency |
| Warm-up time to reach 60% of full light |
| Suitable for accent lighting |
| |

LIFE SPAN

| Nominal life time | 30 000 hrs |
|-----------------------------------------|------------|
| Rated life time | 30 000 hrs |
| Number of switching cycles | 15000 |
| Lumen main.fact.at end of nom.life time | 0,7 |
| Warranty | 3 years |

60370 IE-CL-CLR-15-780-3000K-120-CLR ceiling light 15W 780lm 5999097603704 Ceiling light

780 lm 1000 lm 52 110° 3000K warm white 80 Ra 6 SDCM 2 s N

ELECTRICAL DATA

| Nominal wattage | 15W |
|---------------------|----------|
| Rated wattage | 15W |
| Nominal voltage | 220-240V |
| Operating frequency | 50/60Hz |
| Nominal current | 300 mA |
| Power factor | 0.9 |
| | |
| Overal diameter | 226 mm |
| Overall width | 39 mm |
| Lamp shape | Round |
| Weight | 0,630 kg |
| | |

ADDITIONAL TECHNICAL INFORMATION

| Starting time | 3,0 s |
|---------------------------------------|---------------|
| Optimum operating ambient temperature | -20°C - +40°C |
| Lamp finish | Milky cover |
| Dimming | non-dimmable |
| Energy efficiency class | A+ |
| Energy consumption | 15 kWh/100h |
| Electrical protection class | Class II |
| IP rating | IP20 |
| | |



