## INE'S'A

60372	Nominal wattage	15W
IE-CL-CLR-15-1000-6000K-120	Rated wattage	15W
CLR ceiling light 15W	Nominal voltage	220-240V
5999097603728	Operating frequency	50/60Hz
Ceiling light	Nominal current	300 mA
	Power factor	0.9
	Overal diameter	226 mm
	Overall width	39 mm
1000 lm	Lamp shape	Round
1000 lm	Weight	0,630 kg
67	Mounting	surface
110°		
110°		
6000K		
daylight		
80 Ra		
6 SDCM		
2 s		
Ν		
	IE-CL-CLR-15-1000-6000K-120 CLR ceiling light 15W 5999097603728 Ceiling light 1000 lm 1000 lm 67 110° 110° 6000K daylight 80 Ra 6 SDCM 2 s	IE-CL-CLR-15-1000-6000K-120Rated wattageCLR ceiling light 15WNominal voltage5999097603728Operating frequencyCeiling lightNominal currentPower factorPower factor0veral diameter Overall widthOverall width1000 lmLamp shape1000 lmWeight67Mounting110°110°6000Kdaylight80 Ra6 SDCM2 s2 s

## LIFE SPAN

PRODUCT INFORMATION

Nominal life time	30 000 hrs
Rated life time	30 000 hrs
Number of switching cycles	15000
Lumen main.fact.at end of nom.life time	0,7
Warranty	3 years

## ADDITIONAL TECHNICAL INFORMATION

ELECTRICAL DATA

Starting time	3,0 s
Optimum operating ambient temperature	-20°C - +40°C
Lamp finish	Milky cover
Dimming	non-dimmable
Energy efficiency class	A+
Energy consumption	15 kWh/100h
Electrical protection class	Class II
IP rating	IP20



