# MQ603 Downlight 20W 1650lm 4000K 100° G2



#### PRODUCT INFORMATION

Product code 60498

Product code (long) IE-DL-MQ603-20-1650-4000K-1

Product description MQ603 Downlight 20W 1650lm

EAN code 5999097604985

Category Downlight

#### PHOTOMETRIC DATA

Nominal luminous flux 1650 Lm Rated luminous flux 1650 Lm Nominal beam angle (half-peak value) 100° 100° Rated beam angle (half-peak value) Correlated colour temperature 4000K Colour temperature designation Neutral white 80 Ra Colour rendering index (Ra) 7 SDCM Colour consistency Warm-up time to reach 60% of full light 1 s

## **ELECTRICAL DATA**

Nominal wattage20 WRated wattage20,0 WNominal voltage220-240VOperating frequency50/60HzNominal current100 mAPower factor0.95Wattage of equivalent filament lamp150W

Overal diameter 240 mm
Overall height 53mm
Lamp shape Round
Weight 0,585 kg

#### LIFE SPAN

Nominal life time35000 hRated life time35000 hNumber of switching cycles15000Warranty3 years

## ADDITIONAL TECHNICAL INFORMATION

Starting time 0,5 s
Optimum operating ambient temperature 25°C
Lamp finish Milky cover
Dimming non-dimmable
Energy efficiency class A+
Energy consumption 20,0 kWh/100h

IP rating IP20



