MQ603 Downlight 24W 2000lm 4000K 100° G2



PRODUCT INFORMATION

Product code 60501 IE-DL-MQ603-24-2000-4000K-1 Product code (long) Product description MQ603 Downlight 24W 2000lm 5999097605012 EAN code Category Downlight

PHOTOMETRIC DATA

Nominal luminous flux 2000 Lm Rated luminous flux 2000 Lm Nominal beam angle (half-peak value) 100° 100° Rated beam angle (half-peak value) Correlated colour temperature 4000K Colour temperature designation Neutral white 80 Ra Colour rendering index (Ra) 7 SDCM Colour consistency Warm-up time to reach 60% of full light 1 s

ELECTRICAL DATA

24 W Nominal wattage 24,0 W Rated wattage 220-240V Nominal voltage 50/60Hz Operating frequency Nominal current 120 mA Power factor 0.95 Wattage of equivalent filament lamp 180W

240 mm Overal diameter Overall height 53mm Lamp shape Round Weight 0,610 kg D200-210 mm cutout Mounting

LIFE SPAN

Nominal life time 35000 h Rated life time 35000 h Number of switching cycles 15000 Warranty 3 years

ADDITIONAL TECHNICAL INFORMATION

Starting time 0,5 s Optimum operating ambient temperature 25°C Milky cover Lamp finish non-dimmable Dimming Energy efficiency class 24,0 kWh/100h Energy consumption

IP20 IP rating



