MQ603 Downlight 36W 3000lm 4000K 100° G2



PRODUCT INFORMATION

Product code 60504 IE-DL-MQ603-36-3000-4000K-1 Product code (long) Product description MQ603 Downlight 36W 3000lm 5999097605043 EAN code Category

Downlight

PHOTOMETRIC DATA

Nominal luminous flux 3000 Lm Rated luminous flux 3000 Lm Nominal beam angle (half-peak value) 100° 100° Rated beam angle (half-peak value) Correlated colour temperature 4000K Colour temperature designation Neutral white 80 Ra Colour rendering index (Ra) Warm-up time to reach 60% of full light 1 s

LIFE SPAN

Nominal life time 35000 h Rated life time 35000 h Number of switching cycles 15000 Warranty 3 years

ELECTRICAL DATA

36 W Nominal wattage 36,0 W Rated wattage 220-240V Nominal voltage 50/60Hz Operating frequency Nominal current 160 mA Power factor 0.95 Wattage of equivalent filament lamp 250W

240 mm Overal diameter Overall height 53mm Lamp shape Round Weight 0,645 kg

D200-210 mm cutout Mounting

ADDITIONAL TECHNICAL INFORMATION

Starting time 0,5 s 25°C Optimum operating ambient temperature Milky cover Lamp finish Dimming non-dimmable Energy efficiency class 36,0 kWh/100h Energy consumption

IP rating

IP20



