INESA

PRODUCT INFORMATION

Product code
Product code (long)
Product description
EAN code
Category

PHOTOMETRIC DATA

Nominal luminous flux	3
Rated luminous flux	
Rated useful luminous flux	8
Nominal beam angle (half-peak value)	-
Rated beam angle (half-peak value)	-
Correlated colour temperature	
Colour temperature designation	١
Colour rendering index (Ra)	ł
Colour consistency	(
Warm-up time to reach 60% of full light	(
Suitable for accent lighting	I

LIFE SPAN

Nominal life time	30 000
Rated life time	30 000
Number of switching cycles	>1000
Lumen main.fact.at end of nom.life time	70%
Warranty	3 year

60506 IE-PN-PN60x-45-3600-3000K-1 60x60 45W LED Panel 3000K 5999097605067 Panel Light

3600 lm 3600 lm 80 110° 110° 3000K warm white 80 Ra 6 SDCM 0,5 s Ν

00 hrs 00 hrs 00 ٢S

ELECTRICAL DATA

Nominal wattage	45W
Rated wattage	45W
Nominal voltage	220-240 V
Operating frequency	50/60Hz
Nominal current	210 mA
Power factor	0.9

MECHANICAL DATA

Overall length	595 mm
Overall width	595 mm
Overall height	9mm
Lamp shape	squre
Weight	#HIÁNYZIK

ADDITIONAL TECHNICAL INFORMATION

0,5 s
-10°C - +45°C
non-dimmable
А
45 kWh/100h
Class II
IP20



