

PRODUCT INFORMATION

| | |
|---------------------|--------------------------|
| Product code | 60507 |
| Product code (long) | IE-GT518-120-10800-5700K |
| Product description | GT518 Canopy light 120W |
| EAN code | 5999097605074 |
| Category | Canopy Lighth |

PHOTOMETRIC DATA

| | |
|---|----------|
| Nominal luminous flux | 10800 Lm |
| Rated luminous flux | 10800 Lm |
| Nominal beam angle (half-peak value) | 110° |
| Rated beam angle (half-peak value) | 110° |
| Correlated colour temperature | 5700K |
| Colour temperature designation | Daylight |
| Colour rendering index (Ra) | 70 |
| Warm-up time to reach 60% of full light | 1 s |

LIFE SPAN

| | |
|-------------------|---------|
| Nominal life time | 35000 h |
| Rated life time | 35000 h |
| Warranty | 5 years |

ELECTRICAL DATA

| | |
|---------------------|----------|
| Nominal wattage | 120 W |
| Rated wattage | 120,0 W |
| Nominal voltage | 220 V |
| Operating frequency | 50/60 Hz |
| Nominal current | 570 mA |
| Power factor | 0.95 |

MECHANICAL DATA

| | |
|----------------|-----------|
| Overall length | 500 mm |
| Overall width | 430 mm |
| Overall height | 99 mm |
| Lamp shape | Rectangle |
| Weight | 3.9 kg |

ADDITIONAL TECHNICAL INFORMATION

| | |
|---------------------------------------|--------------|
| Starting time | 1 s |
| Optimum operating ambient temperature | 25° |
| Dimming | Non dimmable |
| Electrical protection class | CLASS I |
| IP rating | IP54 |
| IK rating | IK08 |

