# DL301 Downlight Square 24W 1600lm 3000K 120° G3



#### **PRODUCT INFORMATION**

Product code 60529
Product code (long) IE-DL-DLR300x-24-1600-3000K
Product description DL301 Downlight Square 24W
EAN code 5999097605296

Category Downlight

PHOTOMETRIC DATA

Nominal luminous flux 1600 Lm Rated luminous flux 1600 Lm Nominal beam angle (half-peak value) 120° Rated beam angle (half-peak value) 120° Correlated colour temperature 3000K Colour temperature designation Warm white 80 Ra Colour rendering index (Ra) 6 SDCM Colour consistency

### LIFE SPAN

Nominal life time30000 hRated life time30000 hNumber of switching cycles15000Lumen main.fact.at end of nom.life time70%Warranty3 years

#### ELECTRICAL DATA

Nominal wattage24 WRated wattage24.0 WNominal voltage220-240VOperating frequency50/60 HzNominal current360 mAPower factor0.9

#### MECHANICAL DATA

IP rating

Overall length 301 mm
Overall width 301 mm
Overall height 21 mm
Lamp shape Square
Weight 1,050 kg
Mounting 282 mm x 282 mm cuto

## ADDITIONAL TECHNICAL INFORMATION

Starting time 1,0 s
Optimum operating ambient temperature 25°C
Lamp finish Milky cover
Dimming non-dimmable
Energy efficiency class A+
Energy consumption 24,0 kWh/100h
Electrical protection class CLASS II

IP20



