DL301 Downlight Square 24W 1600lm 4000K 120° G3



PRODUCT INFORMATION

Product code 60530
Product code (long) IE-DL-DLR300x-24-1600-4000K
Product description DL301 Downlight Square 24W
EAN code 5999097605302

Category Downlight

ELECTRICAL DATA

Nominal wattage24 WRated wattage24.0 WNominal voltage220-240VOperating frequency50/60 HzNominal current360 mAPower factor0.9

PHOTOMETRIC DATA

Nominal luminous flux 1600 Lm Rated luminous flux 1600 Lm Nominal beam angle (half-peak value) 120° Rated beam angle (half-peak value) 120° Correlated colour temperature 4000K Neutral white Colour temperature designation 80 Ra Colour rendering index (Ra) 6 SDCM Colour consistency

MECHANICAL DATA

Overall length 301 mm
Overall width 301 mm
Overall height 21 mm
Lamp shape Square
Weight 1,050 kg
Mounting 282 mm x 282 mm cuto

LIFE SPAN

Nominal life time30000 hRated life time30000 hNumber of switching cycles15000Lumen main.fact.at end of nom.life time70%Warranty3 years

ADDITIONAL TECHNICAL INFORMATION

Starting time 1,0 s

Optimum operating ambient temperature 25°C

Lamp finish Milky cover

Dimming non-dimmable

Energy efficiency class A+

Energy consumption 24,0 kWh/100h
Electrical protection class CLASS II
IP rating IP20



